





SPECIFICATIONS

Current Rating: 1.5 Amps
Insulation Resistance: 1000M Ω Min
Contact Resistance: 20mΩ Max
Withstanding Voltage: AC 500V
Operation Temperature: -40° to +105°
Contact Material: Brass
Standard: PA6T
Insulator Material: Polyester (UL 94V-0)
Contact Plating: Gold Flash
Max. Processing Temp: 240° C for 30-60 seconds
(260° C for 5 seconds)



RECOMMEND P. C. B LAYOUT
PCB TOLERANCE: ±0.05 (TOP VIEW)

Shenzhen Kinghelm Electronics Co., Ltd.				www.kinghelm.net				No. of	DIM. A	DIM. B	No. of	DIM. A	DIM. B	No. of	DIM. A	DIM. B	No. of	DIM. A	DIM. B
KH-2.0PH-2X10P-L8.0-SMT				kinghelm666@kinghelm.net				1	0.00	2.00	11	20.00	22.00	21	40.00	42.00	31	60.00	62.00
								2	2.00	4.00	12	22.00	24.00	22	42.00	44.00	32	62.00	64.00
								3	4.00	6.00	13	24.00	26.00	23	44.00	46.00	33	64.00	66.00
								4	6.00	8.00	14	26.00	28.00	24	46.00	48.00	34	66.00	68.00
								5	8.00	10.00	15	28.00	30.00	25	48.00	50.00	35	68.00	70.00
								6	10.00	12.00	16	30.00	32.00	26	50.00	52.00	36	70.00	72.00
								7	12.00	14.00	17	32.00	34.00	27	52.00	54.00	37	72.00	74.00
								8	14.00	16.00	18	34.00	36.00	28	54.00	56.00	38	74.00	76.00
								9	16.00	18.00	19	36.00	38.00	29	56.00	58.00	39	76.00	78.00
								10	18.00	20.00	20	38.00	40.00	30	58.00	60.00	40	78.00	80.00

UNLESS OTHERWISE SPECIFIED TOLERANCE				DRAWN NAME: 2.0PH H2.0 2xnPin SMT PC6.5 PA3.8 PB2.5 L8.0 6T			
X : ±0.30	X° : ±5°	SIZE	A4	SCALE	N:1	PROUCT NO.	
X.X : ±0.25	X.X° : ±1°	REV	A	UNIT	mm	PROJECT	
X.XX : ±0.20	X.XX° : ±0.5°	CHECKED:	陈超凡	2022/04/24	CHECKED:	/ /	APPROVED: / /