


Kinghelm®

REVISIONS					
REV	NUMBER	DESCRIPTION	DWN	CHK	DATE
A		DESIGN	James		9/26



NOTES:

1. ELECTRICAL:

- 1.1. VOLTAGE RATING:DCV 300V 10MS
- 1.2. CONDUCTANCE RESISTANCE: 3.0 OHM/MAX.
- 1.3. INSULATION RESISTANCE: 5.0M OHM/MIN.
- 1.4. THE CABLE SHOULD BE 100% ELECTRICAL TEST
- 1.5. IT SHOULD BE NO ANY OPEN/SHORT, MISWIRING AND INTERMITTENT FAILURES.

2. MATERIAL:


- 2.1. SEE TABLE

3. ALL COMPONENTS ARE RoHS COMPLIANT.

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
④	Sleeving	Black Heat Shrink Tubing, OD: 2.5 × 15mm	1
③	Connector	BNC Male Connector with Male Pin, Straight Type, Nickel-Plated	1
②	Terminal	High Imitation I-PEX 178 Terminal, Gold-Plated	1
①	Coaxial Cable	RG178 Cable, Color: Brown, OD: 1.80mm	AS

Shenzhen Kinghelm Electronics Co., Ltd.

www.kinghelm.net

ALL DIMENSION ARE IN MM	DRAWN James	DATE 2023-3-8	KH-BNC-RG178IPEX-100 TITLE			
	CHKD. Frank	2023-3-8				
COMPUTER GENERATED IN SOLIDWORKS DO NOT SCALE THIS DRAWING	APPD. Scott	2023-3-8	RG178 CABLE IPEX TO BNC/M, L=100MM			
PROJECTION 	GENERAL TOLERANCE FOR ANGLES X.X X.XX X.XXX ±1° ±0.3 ±0.25 ±0.150		SIZE B	DWG Number.		REV A
			SCALE:Free		TYPE	SHEET 1 OF 1

CUSTOMER P/N: