



1. ELECTRICAL:

- 1.1. VOLTAGE RATING:DCV 300V 10MS
- 1.2. CONDUCTANCE RESISTANCE: 3.0 OHM/MAX.
- 1.3. INSULATION RESISTANCE: 5.0M OHM/MIN.
- 1.4. THE CABLE SHOULD BE 100% ELECTRICAL TEST
- 1.5. IT SHOULD BE NO ANY OPEN/SHORT, MISWIRING AND INTERMITTENT FAILURES

2. MATERIAL:

- 2.1. SEE TABLE
3. ALL COMPONENTS ARE RoHS COMPLIANT.

ITEM NO.	PART NUMBER	DESCRIPTION	QTY
③	Tubing	Black heat shrink tubing OD:3.5*15MM	2
②	Connector	FAKRA connector female header with female pin, blue housing, Type C	2
①	Coaxial Cable	174 coaxial cable, black sheath, OD: 2.8mm	AS

Shenzhen Kinghelm Electronics Co., Ltd.

www.kinghelm.net

ALL DIMENSION ARE IN MM	DRAWN Jamy	DATE 2024-06-17	
	ENG. ALAN	2024-06-17	
COMPUTER GENERATED IN SOLIDWORKS	MFG. KEN	2024-06-17	
DO NOT SCALE THIS DRAWING	Q.A. TONY	2024-06-17	
PROJECTION 	GENERAL TOLERANCE FOR ANGLES X.X X.XX ± 1° ± 0.13 0.25 0.150		SIZE Number B X.XXX
			REV A
SCALE: Free TYPE			SHEET 1 of 1