

3
2
1

ZONE REV. DESCRIPTION APPROVAL DATE

RoHS

Compliant

Performance:

Rated current: 1.0A

Rated voltage: 12V

Withstand voltage: 500V

Contact resistance: 30mΩ MAX


Insulation resistance: 500MΩ

Operating temperature: -40 ~ +85

Plastic part (Material): LCP E130I

Contact point (Material): Copper alloy,
contact gold-plated 3μm

PART NO.	DIM A	DIM B
KH-12701-2P225		
KH-12701-3P225		1.27
KH-12701-4P225	5.08	2.54
KH-12701-5P225	6.35	3.81
KH-12701-6P225	7.62	5.08



Shenzhen Kinghelm Electronics Co., Ltd

KH-12701-3P170

www.kinghelm.net

DESIGN	X. Z. Huang	SCALE		
DRAWING	X. Z. Huang	UNIT	mm	
CHECK	X. X. Zheng	SIZE	A4:210:297	
APPROVAL	M. Y. Li	VER.	01	

TOLERANCE
X. ±0.35
X. X ±0.25
X. XX ±0.15
ANGLE ±3°

PART NAME	Battery Holder
PART NO.	KH-12701 Series
DWG. NO	RBD-SP-0019
DATE	2019-11-04