


Kinghelm®

REVISIONS					
REV	NUMBER	DESCRIPTION	DWN	CHK	DATE
A		DESIGN			



NOTES:

1. ELECTRICAL:

- 1.1. VOLTAGE RATING:DCV 300V 10MS
- 1.2. CONDUCTANCE RESISTANCE: 3.0 OHM/MAX.
- 1.3. INSULATION RESISTANCE: 5.0M OHM/MIN.
- 1.4. THE CABLE SHOULD BE 100% ELECTRICAL TEST
- 1.5. IT SHOULD BE NO ANY OPEN/SHORT, MISWIRING AND INTERMITTENT FAILURES.

2. MATERIAL:

2.1. SEE TABLE

3. ALL COMPONENTS ARE RoHS COMPLIANT.

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
	INTERFACE	Fourth-generation IPEX terminal	1
	COAXIAL CABLE	RG0.81 CABLE,COLOR: BLUE,OD: 0.81mm	AS

Shenzhen Kinghelm Electronics Co., Ltd.

www.kinghelm.net

KH-IPEX4-221-RG0.81-BU300

ALL DIMENSION
ARE IN MM

DRAWN
Jamy

DATE
2020-6-15

ENG.

COMPUTER GENERATED
IN SOLIDWORKS


MFG.

DO NOT SCALE
THIS DRAWING

QA.

Fourth-Generation IPEX to Open RG0.81 Blue Adapter Cable

PROJECTION



GENERAL TOLERANCE FOR
ANGLES X.X X.XX X.XXX
±1° ±0.3 ±0.25 ±0.150

SIZE Number

B

REV

A

SCALE:Free

TYPE

SHEET 1 OF 1

CUSTOMER P/N: