


Kinghelm®

REVISIONS					
REV	NUMBER	DESCRIPTION	DWN	CHK	DATE
A		DESIGN			



NOTES:

1. ELECTRICAL:


- 1.1. VOLTAGE RATING:DCV 300V 10MS
- 1.2. CONDUCTANCE RESISTANCE: 3.0 OHM/MAX.
- 1.3. INSULATION RESISTANCE: 5.0M OHM/MIN.
- 1.4. THE CABLE SHOULD BE 100% ELECTRICAL TEST
- 1.5. IT SHOULD BE NO ANY OPEN/SHORT, MISWIRING AND INTERMITTENT FAILURES.

2. MATERIAL:

- 2.1. SEE TABLE
3. ALL COMPONENTS ARE RoHS COMPLIANT.

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
③	Casing	OD:2.5* 15 mm Casing	1
②	Connector	SMA male straight connector Male pin,Gold plated	1
①	Coaxial cable	RG1.78 brown coaxial cable,OD:1.78mm	AS

Shenzhen Kinghelm Electronics Co., Ltd

ALL DIMENSION ARE IN MM	DRI	DATE	KH-SMAJ-221-RG1.78-180		
	DRAIN. Jamy	2023/8/11			
COMPUTER GENERATED IN SOLIDWORKS	CHK. Alan	2023/8/11			
DO NOT SCALE THIS DRAWING	APP. Ellis	2023/8/11	www.kinghelm.net		
PROJECTION 	GENERAL TOLERANCE FOR ANGLES X.X X.XX X.XXX ± 1° ± 0.3 ± 0.25 ± 0.150				
			SCALE: Free	TYPE	SHEET 1 OF 1