


Kinghelm®

REVISIONS					
REV	NUMBER	DESCRIPTION	DWN	CHK	DATE
A		DESIGN			



NOTES:

1.ELECTRICAL:

- 1.1.- VOLTAGE RATING: DCV 100V 10MS
- 1.2.- CONDUCTANCE RESISTANCE:3.0 OHM/MAX.
- 1.3. INSULATION RESISTANCE: 20M OHM/MIN.
- 1.4.- THE CABLE SHOULD BE 100% ELECTRICAL TEST
- 1.5- IT SHOULD BE NO ANY OPEN/SHORT,
- MISWIRING AND INTERMITTENT FAILURES.

2. MATERIAL:

2.1. SEE TABLE

3.ALL COMPONENTS ARE RoHS COMPLIANT.


ITEM NO.	PART NUMBER	DESCRIPTION	QYT.
④	Casing	Black heat-shrinkable sleeve,2*15MM	AS
③	Connector	3rd Generation IPEX 0.81 Domestic Terminal	1
②	Connector	SMA Female Connector with Female Pin, Elbow Type, 11 Threads, Gold-Plated	1
①	Coaxial Cable	RF0.81 Black Cable, OD: 0.81mm	AS

Shenzhen Kinghelm Electronics Co., Ltd.

KH-SMAKW-IPEX3-RG0.81-B60

www.kinghelm.net

ALL DIMENSION ARE IN MM	DRAWN	Jamy	DATE	2019 /03 /01
	ENG.			
	COMPUTER GENERATED IN SOLIDWORKS	MFG.		
	DO NOT SCALE THIS DRAWING	Q.A.		



GENERAL TOLERANCE FOR
ANGLES X.X X.XX X.XXX
± 1° ± 0.3 ± 0.25 ± 0.150

SIZE	Number	REV
B		A
SCALE: Free	TYPE	SHEET 1 OF 1

CUSTOMER P/N: