


Kinghelm®

REVISIONS					
REV	NUMBER	DESCRIPTION	DWN	CHK	DATE
A		DESIGN			



NOTES:

1. ELECTRICAL:

- 1.1. VOLTAGE RATING: DCV 100V 10MS
- 1.2. CONDUCTANCE RESISTANCE: 3.0 OHM/MAX.
- 1.3. INSULATION RESISTANCE: 20M OHM/MIN.
- 1.4. THE CABLE SHOULD BE 100% ELECTRICAL TEST
- 1.5. IT SHOULD BE NO ANY OPEN/SHORT, MISWIRING AND INTERMITTENT FAILURES.

2. MATERIAL:

- 2.1. SEE TABLE

3. ALL COMPONENTS ARE RoHS COMPLIANT.

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
④	Casing	Black heat-shrinkable sleeve, 2*15MM	AS
③	Connector	4rd Generation IPEX 0.81 Domestic Terminal	1
②	Connector	SMA Female Connector with Female Pin, Elbow Type, 11 Threads, Gold-Plated	1
①	Coaxial Cable	RF0.81 Black Cable, OD: 0.81mm	AS

Shenzhen Kinghelm Electronics Co., Ltd.

KH-SMAKW-IPEX4-RG0.81-B250

www.kinghelm.net

ALL DIMENSION ARE IN MM	DRAWN Jamy	DATE 2019 /03 /01
	ENG.	
COMPUTER GENERATED IN SOLIDWORKS	MFG.	
	Q.A.	
DO NOT SCALE THIS DRAWING		

PROJECTION	GENERAL TOLERANCE FOR		
	ANGLES	X.X	X.XX
	± 1°	± 0.3	± 0.25
		± 0.150	

SIZE	Number	REV
B		A
SCALE: Free	TYPE	SHEET 1 OF 1

CUSTOMER P/N: