



3	SHELL	C5191	T=0.30	≤Cu 120U" + ≤Ni 100U"	1
2	TERMINAL	C2680	T=0.25	Sn 100U" + Au 1u" - 30U"	4
1	HOUSING	PBT	—	WHITE/BLACK UL94-V0	1
NO.	PART NAME	MATERIAL	THICK	FINISH	Q'TY

- NOTE:
- 1.1 Contact resistance: 30 MΩ Max
  - 1.2 Insulation resistance: 1000 MΩ Min
  - 1.3 Dielectric voltage: 500V AC one sec level in
  - 1.4 Operating temperature: -55°C ~ +105°C
  - 1.5 Total mating force: 3.5 Kgf Max.
  - 1.6 Total unmating force: 1.0 Kgf Min.
  - 1.7 Major DIM: Δ

Δ	DWG issued	SIGN	DATE
REV	MODIFICATION		

Common tolerance		CHARTING	SHENZHEN KINGHELM ELECTRONIC CO., LTD.	WWW.BDS666.COM	SHEET	OF
X.	±0.50	CHECKED	KH-AF180WJ-13	0755-83044319	UNIT	mm
.X	±0.20	APPROVAL			PRODUCT NAME	SCALE
.XX	±0.10	VIEW	Part Number	DWG NO.		
X° ±2.0°						
.X° ±1.0°						
.XX° ±0.5°						