


Kinghelm®

REVISIONS					
REV	NUMBER	DESCRIPTION	DWN	CHK	DATE
A		DESIGN			



Three components are delivered with accessories (Waterproof ring, washers and nut)

NOTES:

1. ELECTRICAL:
 - 1.1. VOLTAGE RATING:DCV 300V 10MS
 - 1.2. CONDUCTANCE RESISTANCE: 3.0 OHM/MAX.
 - 1.3. INSULATION RESISTANCE: 5.0M OHM/MIN.
 - 1.4. THE CABLE SHOULD BE 100% ELECTRICAL TEST
 - 1.5. IT SHOULD BE NO ANY OPEN/SHORT, MISWIRING AND INTERMITTENT FAILURES
2. MATERIAL:
 - 2.1. SEE TABLE
3. ALL COMPONENTS ARE RoHS COMPLIANT.

ITEM NO.	PATR NUMBER	DESCRIPTION	QTY
④	Tube	Black Heat-shrink Tube, OD:2.0MM	AS
③	Terminal	High-quality Copy I-PEX 1.13 Terminal, gold-plating	1
②	Joint	Waterproof RP-SMA-K, split-type with 12 screws, gold-plating	1
①	Coaxial Cable	RF1.13 Gray Cable, OD:1.13mm	AS

SHENZHEN KINGHELM ELECTRONIC CO., LTD.		WWW.BDS666.COM	
KHB65-37(11)-28-A/3		0755-83044319	
ALL DIMENSION ARE IN MM	DRAWN Jamy	DATE 2018/09/24	I-PEX 1.13 TO Waterproof RP-SMA-K with 12 screws, gold-plating L=65MM
	ENG.		
COMPUTER GENERATED IN SOLIDWORKS	MFG.		
DO NOT SCALE THIS DRAWING	Q.A.		
PROJECTION	GENERAL TOLERANCE FOR ANGLES		SIZE B
	± 1° ± 0.3 ± 0.25 ± 0.150		Number
CUSTOMER P/N:			REV A
			SCALE: Free
			TYPE
			SHEET 1 OF 1

立刻移除水印