

| | | |
|----------------------------|-------------|----------------------|
| CUSTOMER : | | Customer Part NO. |
| | | Part Descripon |
| Item | | Specification |
| NO. of conductors | N | 6P-96P |
| Pitch | P | 0.5±0.05 |
| Total Pitch | PT | 2.5-47.5±0.08 |
| Total Length | L | 25-20000±2 |
| Insulation Length | IL | 25-20000±2 |
| Margin Width | M | 0.5±0.08 |
| Total Width | W | 3.5-48.5±0.08 |
| Strip Length | S1 | 1.5-5±0.5 |
| Strip Length | S2 | 1.5-5±0.5 |
| Reinforeing tape length | B1 | 2.5-30±2 |
| Reinforeing tape length | B2 | 2.5-30±2 |
| Slanting | A | ≤0.3 |
| Over lap | | / |
| Terminal thickness | t1 | 0.3±0.02 |
| Thickness insulation | t | 0.12±0.02 |
| Conductor thickness | Ct | 0.035±0.01 |
| Conductor width | Cw | 0.3±0.03 |
| Supporting Tapc Color | Blue | |
| PET(Supporting Tapc Color) | 0.225mm | |
| PET(Insulation) | 0.043mm | |
| PET(Insulation) | 0.043mm | |
| Rev | A | |



| | | | |
|--|---------------------------------------|-------------------|----------------|
| Storage condition :Recommended: | | | |
| Temp:15° C~25° C | | Humidity:30~60RH% | |
| Drawing Not TO Scale Hidden Lines Not Shown | Discharge Date | Review Date | Drawing NO |
| | 2021-05-19 | | |
| Unit(单位):mm | SHENZHEN KINGHELM ELECTRONIC CO., LTD | | WWW.BDS666.COM |
| | KH-FFC-A0.5-24P-100MM | | 0755-83044319 |