

CUSTOMER :		Customer Part NO.				
		Part Descripon				
Item	Specification					
NO. of conductors	N					6P-96P
Pitch	P					0.5 ± 0.05
Total Pitch	PT					2.5-47.5 ± 0.08
Total Length	L					25-20000 ± 2
Insulation Length	IL					25-20000 ± 2
Margin Width	M					0.5 ± 0.08
Total Width	W					3.5-48.5 ± 0.08
Strip Length	S1					1.5-5 ± 0.5
Strip Length	S2					1.5-5 ± 0.5
Reinforeing tape length	B1					2.5-30 ± 2
Reinforeing tape length	B2					2.5-30 ± 2
Slanting	A					≤ 0.3
Over lap						/
Terminal thickness	t1					0.3 ± 0.02
Thickness insulation	t					0.12 ± 0.02
Conductor thickness	Ct					0.035 ± 0.01
Conductor width	Cw					0.3 ± 0.03
Supporting Tape Color	Blue	Temp:15° C~25° C		Humidity:30~60RH%		
PET(Supporting Tape Color)	0.225mm	Drawing Not TO Scale Hidden Lines Not Shown	Discharge Date	Review Date	Drawing NO	
PET(Insulation)	0.043mm Printing	<p>Unit:mm</p>	2021-05-19			
PET(Insulation)	0.043mm White		SHENZHEN KINGHELM ELECTRONIC CO., LTD.		WWW.BDS666.COM	
Rev	B		KH-FFC-V0.5-18P-100MM		0755-83044319	