

CUSTOMER :		Customer Part NO.						
		Part Descripon						
Item	Specification							
NO. of conductors	N					6P-96P		
Pitch	P					0.5±0.05		
Total Pitch	PT					2.5-47.5±0.08		
Total Length	L					25-20000±2		
Insulation Length	IL					25-20000±2		
Margin Width	M					0.5±0.08		
Total Width	W					3.5-48.5±0.08		
Strip Length	S1					1.5-5±0.5		
Strip Length	S2					1.5-5±0.5		
Reinforeing tape length	B1					2.5-30±2		
Reinforeing tape length	B2					2.5-30±2		
Slanting	A					≤0.3		
Over lap						/		
Terminal thickness	t1					0.3±0.02		
Thickness insulation	t					0.12±0.02		
Conductor thickness	Ct					0.035±0.01		
Conductor width	Cw					0.3±0.03	Storage condition :Recommended:	
Supporting Tapc Color	Blue					Temp:15° C~25° C	Humidity:30~60RH%	
PET(Supporting Tapc Color)	0.225mm					Drawing Not TO Scale Hidden Lines Not Shown	Discharge Date	Review Date
PET(Insulation)	0.043mm		2021-05-19					
PET(Insulation)	0.043mm		SHENZHEN KINGHELM ELECTRONIC CO., LTD		WWW.BDS666.COM			
Rev	A	Unit(单位):mm	KH-FFC-A0.5-32P-100MM		0755-83044319			