



### Specification

1. Material: stainless steel SUS301, T = 0.10 ± 0.005;
2. The welding and contact surfaces of the Tin terminal shall be free of burrs, and the maximum size of burrs in other parts shall be 0.03mm;
3. Twisting: 45 ° / 1000mm, arch 5mm/1000mm;
4. Dimensions marked with "▲" shall be measured and inspected with emphasis;
5. Unmarked R Max R0.13;
6. Electroplating must be inspected by 48-hour salt spray test;
7. Life test > 20000 times The elasticity of the product shall be between 60gf and 80gf as required.
8. Ni 50~80u"min, soldering area gold-plating, contact area gold plating 1U"MIN

Rev.	ECN Number	Description	Date	Drawn	Checked	Approved

Dimensional Tolerance ±0.05

SHENZHEN KINGHELM ELECTRONIC CO., LTD.

WWW.BDS666.COM

KH-302015-TP

0755-83044319

GENERAL TOLERANCE

XX. ±0.50

X. ±0.35

.X ±0.25

.XX ±0.15

SCALE:

1:1

DRAWN

CHECK

APPROVE

DATE

DATE

DATE

DWG. NO.

681-0039B-2

TITLE

Customer's drawing

REV.

A

SHEET

1/1

PARTS NO.(INTENDED USE)

JXH0039B2

S4 Spring, SMT, B type

L3.0\*W2.0\*H1.50mm

